



Advanced microscopy of multicomponent functional materials: The merit of utilizing routine electron microscopes

Zhang, Wei

Publication date:
2011

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Zhang, W. (2011). *Advanced microscopy of multicomponent functional materials: The merit of utilizing routine electron microscopes*. Abstract from 62nd Annual Meeting of Scandinavian Microscopy Society, Oulu (FI), 8-10 Jun.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Advanced microscopy of multicomponent functional materials: The merit of utilizing routine electron microscopes

W. Zhang

Fuel Cells and Solid State Chemistry Division, Risø National Laboratory for Sustainable Energy, 4000
Roskilde, Denmark

The routine electron microscopes are still playing an important role in materials science and inorganic chemistry although significant progress has been made in microstructure characterization by applying Cs-corrected electron microscopy. Here I give several research cases.

First, based on electron beam induced deposition in a high-vacuum SEM using $\text{Fe}(\text{CO})_5$, a cellular film of iron nanocrystals has been successfully fabricated through a detailed microscopy analysis. Second, an imaging strategy for surfaces is proposed that involves adjusting the contrast transfer function of TEM to either atomic details of individual basic structural units or to the supramolecular assembly of basic structural units of crystal. The imaging strategy can be applied to other issues involving structures with large unit cells (e.g., complex MoVTenNbO_x catalyst) and does not require special high-end instrumentation. Third, a new phase-change mechanism was proposed by combining microstructure investigations of phase-change GeSbTe alloy with the thermodynamics analysis of system. Forth, an unusual martensitic transformation from HCP α -Ti to BCC β -Ti twinning induced by rapid heating was achieved in a popular Ti-6Al-4V alloy under an electropulsing, which agrees well with the phenomenological crystallographic theory of martensitic transformation.

The aforementioned methods and analysis can be extended to the emerging field of solid oxide fuel cell, and may contribute to revealing some new relevant physics/chemistry.

I would like to express my sincere thanks to the instructive directions of several supervisors and contributions of many colleagues from NIMS, FHI-MPG, SAIT and IMRCAS. Dr. L.T. Kuhn is greatly acknowledged for her enthusiastic support.